



Republic of the Philippines  
GENERAL SANTOS CITY WATER DISTRICT  
E. Fernandez Street, Barangay Lagao General Santos  
Telephone No.: 552-3824; Telefax No.: 553-4960  
Email Address: gscwdprocurement@yahoo.com

GPM-014-2

**REQUEST FOR QUOTATION**

RFQ #: 3-0220-018      DATE: 02/05/2020

SUPPLIER: \_\_\_\_\_  
ADDRESS: \_\_\_\_\_  
TELEPHONE NO. : \_\_\_\_\_  
TIN NO. : \_\_\_\_\_

Dear Sir/Madam,

Pls. quote your lowest price on the item/s listed below subject to general condition stating the shortest time of delivery and submit your quotation duly signed by your representative not later than 02/11/2020, Pls. furnish this office the following articles subject to the terms and conditions contained therein.

ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	WATER BATH : PLEASE SEE ATTACHED SPECIFICATIONS-ABC: PHP 200,000.00 ##### nothing follows #####	1	unit	P

Date of Delivery: \_\_\_\_\_  
Price Validity : \_\_\_\_\_  
Terms of Payment: \_\_\_\_\_

Place of Delivery: GSCWD Bodega  
\*\*\*\*No partial delivery allowed\*\*\*\*  
Note: 6% WITHHOLDING TAX DEDUCTION  
PR NO.: 0120-109

Requested by:

Price quoted by:

\_\_\_\_\_  
Supplier

\_\_\_\_\_  
Date

**GESE M. BANGS**  
MANAGER  
OFFICE A




SAMPLE PHOTOS OF WATER BATHS

**WATER BATH SPECIFICATIONS:**

- CAPACITY : 28-30 LITERS
- OPERATING TEMPERATURE RANGE: Ambient +10 °C to +95 °C
- EXTERIOR: STAINLESS STEEL CASING
- INTERIOR: Easy-to-clean interior, made of stainless steel
- INCLUSION OF STAINLESS STEEL GABLE COVER
- Digital Temperature Controller
- Calibration capability
- Primary and automatic safety thermostats
- TEMPERATURE STABILITY: 0.1 °C
- TEMPERATURE VARIATION: +/-0.1 °C
- SAFETY:
  - Temperature control mechanical temperature limiter TB protection class 1 switching the heating off at approx. 30°C above max. temperature of the bath
  - Temperature control in case of over temperature due to failure, the heating is switched off at approx. 10°C above the set temperature (fixed value)
- ELECTRICAL DATA:
  - Voltage 230 V, 50/60 Hz
  - Electrical load approx. 2400 W (during heating)
- NATURAL CIRCULATION WITH TEMPERATURE CONTROLLER

Prepared by:

  
**MA. RITA B. BARRIESES, RMT**  
Section Head - Laboratory