

### Republic of the Philippines GENERAL SANTOS CITY WATER DISTRICT

E. Fernandez Street, Barangay Lagao General Santos Telephone No.: 552-3824; Telefax No.: 553-4960 Email Address: gscwdprocurement@yahoo.com

#### **REQUEST FOR QUOTATION**

DATE:

RFQ #:3-0220-023

02/11/2020

ADDRESS: TELEPHONE NO. :				
stating the sh representative	e your lowest price on the item/s listed hortest time of delivery and submit you not later than 02/17/2020, Pls. furnish terms and conditions contained therein.	elow suk r quotat this off	oject to tion dul tice the	general condition.y signed by you following article
ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	LABOR & MATERIALS* : FLEXIBORE HOSE ASSEMBLY WITH COMPLETE ACCESSORIES- SEE ATTACHED SCOPE OF SUPPLY-ABC: PHP 520,000.00 ########## nothing follows ####################################	1	LOT	P
Date of Delivery: Price Validity : Perms of Payment: Place of Delivery: *****No partial de Note: 6% WITHHOLDI PR NO.: Requested by:	elivery allowed****	Price q	uoted by:	
kequested by:		Price quoted by:		
			Supp	olier
	Agnes P Tampico		I	Date



## Republic of the Philippines GENERAL SANTOS CITY WATER DISTRICT

E. Fernandez St., Lagao, General Santos City

### **SCOPE OF SUPPLY**

TITLE: <u>Supply, Delivery and Installation of Flexible hose for Pumping Station</u>
<u>No. 20, Templado Compound, Brgy. Calumpang.</u>

#### I. Description

The scope of work shall be supply, delivery and installation of flexible hose assembly to be utilized as riser of submersible pump and motor.

#### II. Scope of Work

- 1. Provide necessary tools and equipment.
- 2. Provide trained technicians to conduct the installation.
- 3. Provide personal protective equipment for the personnel that will be performing the activity.
- 4. Perform commissioning of the newly installed unit.

#### III. Scope of Supply

1. Flexible Riser Specification

a. Nominal size : 6 inches (150mm)

b. Length : 60 meters c. Burst pressure : 44 bars d. Peak Tensile load : 16 tonnes

e. Weight : 2.5 kg/m

f. Maximum diametric swell : 15% g. Maximum operating temperature : 60°C

h. Water pH range : 3 to 9 i. Safety Factor : 2:1

j. Made of tough Polyurethane Cover

k. With woven Polyester Fabric

1. Strips with loop every meter to secure power cable

m. Impregnated Polyurethane lining bonded to outer to eliminate separation.

n. Potable Water Approval : AS4020

2. Flexible Coupling : 2 PCS, 304 SS, CODE CF60A

3. Flexible Cable Ties : 140pcs

4. Flexible Break-off Plug : 1 set, Fitted, CODE BO00F

#### IV. Terms & Conditions

1. The customer GSCWD shall not be held liable for any damage in the equipment or tools incur during the said activity.



# Republic of the Philippines GENERAL SANTOS CITY WATER DISTRICT

E. Fernandez St., Lagao, General Santos City

- 2. Our maintenance personnel will be assisting your technicians in the field.
- 3. All relevant or incidental cost like food and allowances of the personnel shall be borne entirely by the supplier.
- 4. Warranty of the flexible hose including accessories shall be one (1) year from the date of commissioning.

Prepared by:

DLUANIE R. ENERIO, ME

WUDO-

Checked and Approved by:

ROGELIO A. BESANA JR. C.E./RMP

Department Manager A - Engineering & Construction