

## Republic of the Philippines **GENERAL SANTOS CITY WATER DISTRICT**

E. Fernandez St. Lagao, General Santos City Telephone No. (083) 552-3824/ Telefax No. (083) 553-4960 E-mail Address: gscwaterdistrict@yahoo.com



**EXPLORATORY / DRILLING OF PRODUCTION WELL** 

Location: LANDERO LOT, BRGY. MABUHAY, GSC

Owner:

**GENERAL SANTOS CITY WATER DISTRICT** 

Subject: BILL OF QUANTITIES

Item No.	Particulars	200m DEPTH USING 300mmØ (12") SCREEN				
		Qty.	Unit	Unit Cost	Amount	
A.	PREPARATION OF SITE AND SETTING UP OF EQUIPMENT					
A.1	Excavation of concrete foundation of rig, mudpit, canal and guide borehole	1	lot			
A.2	Concreting of foundation for rig and around the conductor pipe casing	1	lot			
A.3	Grouting of mudpit and canal	1	lot			
A.4	Setting-up of equipment including test run	1	lot		9	
В.	DRILLING OF 200mmØ PILOT HOLE x 200m. (Including strata sampling every one meter penetration or less whenever change of formation occurs including installation of temporary casings if necessary.)	200	l.m.			
c.	GEOPHYSICAL BOREHOLE LOGGING OF PILOT HOLE (Soil analysis, water bearing strata identification, final well design, geophysical borehole logging (self potential and electrical resistivity)	1	lot			
D.	REAMING OF PILOT HOLE FROM 200mmØ TO 600mmØ					
D.1	Reaming of 450mm (17") borehole	200	l.m.			
D.2	Reaming of 600mm (24") borehole	200	l.m.			
<b>E.</b>	FURNISHING OF SPIRAL WELDED STEEL CASING AND CONTINUOUS WIREWOUND STAINLESS STEEL SCREEN			,		

Item No.	Particulars	200m DEPTH USING 300mmØ (12") SCREEN				
		Qty.	Unit	Unit Cost	Amount	
E.1	400mmØ (16") Spiral Welded Steel pipe, minimum thickness is 9.00mm	101	l.m.			
E.2	300mmØ (12") Spiral Welded Steel pipe, minimum thickness is 9.00mm	54	l.m.			
E.3	300mmØ (12") Stainless steel continUous slot, wedge wirewound well screen, slot size 1.5mm (slot 60)	45	l.m.			
E.4	400mmØ x 300mmØ x 1.00m Steel Reducer	1	pc.			
F.	INSTALLATION OF CASINGS AND SCREENS INCLUDING STICK-UP PIPE 181 meters)	201	l.m.		POLICE MARCHANIA CONTRACTOR CONTR	
G.	FURNISHING AND INSTALLATION OF CASING CENTRALIZER	6	pc.	4		
Н.	FURNISHING AND INSTALLATION OF GRAVEL PACK AND GRAVEL FILL PIPE	1	lot			
l.	TREATMENT WITH POLYPHOSPHATE SOLUTION	1	lot		•	
J.	WELL DEVELOPMENT					
J.1	Surging/Brushing	12	hour		<i>y</i>	
J.2	Jetting/ Backwashing	12	hour			
J.3	Airlift Method	12	hour			
K.	STEP DRAWDOWN TEST, Max. Q = 70lps	1	lot			
L.	CONTINUOUS CONSTANT DISCHARGE RATE PUMPING TEST, Q = 70lps	72	hour		M. M. Marian	
M.*	CEMENT GROUTING OF ANNULUS GROUND (25 m. DEPTH)	25	l.m.			
N.	FURNISHING AND INSTALLATION OF WELL HEAD CAP AND SOUNDING TUBE	1	lot			
0.	WATER QUALITY TESTING					
0.1	Physical and Chemical analysis (13 Parameters of PNSDW)	1	sample			
0.2	Bacteriological Analysis	1	sample			

Item No.	Particulars	200m	200m DEPTH USING 300mmØ (12") SCREEN				
		Qty.	Unit	Unit Cost	Amount		
0.3	Pesticide Analysis	1	sample				
0.4	Heavy Metal Test	1	sample				
Р.	Well Camera after Well Rehabilitation	1	lot				
Q.	SPECIAL ITEM				3		
Q.1	Provision of Field Office for Resident Engineer	1	lot				
Q.2	Project Signboard (GSCWD and COA)	2	set				
Q.3	Occupation Safety and Health Program	1	lot				
Q.4	Mobilization and Demobilization	1	lot				
	TOTAL ESTIMATED PROJECT COST				_		

B. I		
a i		
N		

NOTE:						
PLEASE REFER TO SPECIFICATIONS AND APPROVED PLAN FO	R FURTHER DETAILS					
Submitted by:						
Name of Bidder representative:						
Position:						
Name of Bidder:						