



Republic of the Philippines  
GENERAL SANTOS CITY WATER DISTRICT  
E. Fernandez Street, Barangay Lagao General Santos  
Telephone No.: 552-3824; Telefax No.: 553-4960  
Email Address: gscwdprocurement@yahoo.com

GPM-014-4

## **REQUEST FOR QUOTATION**

RFQ #: **3-0525-090**

DATE: **5/27/2025**

SUPPLIER: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

TELEPHONE NO. : \_\_\_\_\_

TIN NO. : \_\_\_\_\_

Dear Sir/Madam,

Pls. quote your lowest price on the item/s listed below subject to general condition stating the shortest time of delivery and submit your quotation duly signed by your representative not later than 6/2/2025, Pls. furnish this office the following articles subject to the terms and conditions contained therein.

**Instructions :**

1. Accomplish this Request for Quotation duly, correctly, and completely.
2. Do not alter the contents of this form in any way.
3. If Technical Specifications/ Terms of Reference is provided, prospect bidder (supplier / service provider) must indicate and signify compliance to every perimeter in the specification.

ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	CONSTRUCTION/LABOR AND MATERIALS : PLEASE SEE ATTACHED SCOPE OF WORK-ABC: PHP 251,716.91 ##### nothing follows #####	1	LOT	P

Delivery Term: \_\_\_\_\_

Price Validity : \_\_\_\_\_

Mode of Payment: \_\_\_\_\_

Place of Delivery: GSCWD Bodega

\*\*\*\*\*No partial delivery allowed\*\*\*\*

Note: 6% WITHHOLDING TAX DEDUCTION

PR NO.: 0425-059

Requested by: \_\_\_\_\_

Price quoted by: \_\_\_\_\_

\_\_\_\_\_  
Supplier

\_\_\_\_\_  
Date

  
Andrew H. Nadal,  
Material Procurement Officer A



Republic of the Philippines  
**GENERAL SANTOS CITY WATER DISTRICT**  
E. Fernandez St., Brgy. Lagao, General Santos City  
Telephone No. (083) 552-3824/ Telefax No. (083) 553-4960  
[www.gensanwater.gov.ph](http://www.gensanwater.gov.ph)



## SCOPE OF WORK

Project Title: **CONSTRUCTION OF ROADWAY PERIMETER FENCE AT PS #27**

Location: **Landero Lot, Brgy. Mabuhay, General Santos City**

1. The winning bidder shall provide/supply all necessary materials, labor and equipment and other necessary items to complete the construction of the said project.
2. All works shall be performed by the winning bidder in accordance with the approved plan and specifications of the owner as enumerated below.

### 2.1 Site Preparation

The location of the building where is to be erected shall be staked out and grade established as shown on drawings and in accordance with the Local Building Code. Contractor shall provide instrument for purposes of establishing, checking, and monitoring of the elevation and plumbness.

### 2.2 Clearing and Grubbing

All surface objects and all trees, stumps, roots and other protruding obstructions, not designated to remain, shall be cleared and/or grubbed.

### 2.3 Earthworks

Excavation shall include the removal of materials of whatever nature encountered that would interfere with the proper execution and completion of the work. All excavations shall be carried to the grade of the bottom of the footing or slab or as indicated on technical drawings. The materials excavated shall be place as backfill on the footing, etc. and above shall be compacted as described. Excess will be hauled to a place designated by the Owner.

### 2.4 Concrete Works

Cement shall conform to the "Standard specifications for Portland Cement "(ASTM C-150-Latest Revision) and shall be type I. The cement shall be in accordance with DPWH standards such as "Holcim, Royal, Hex cement or other brands of the same quality" and shall not be more than three (3) months from date of manufacture.

All reinforcing steel bars used shall be of deformed type, new, free from rust, oil, defects, greases or kinks. They shall conform to the latest edition of National Structural Code for Buildings with a minimum grade equal to 275 Mpa (Grade 40) unless otherwise shown on the plans. Stamp Mark and Color Coding shall also in accordance to its corresponding Grade. Test of



this materials, to determine its suitability shall be in accordance with the standards of the American Society for Testing and Materials (ASTM).

## **2.5 Masonry Works**

The work includes, furnishing labor, equipment and materials performing all operations required to complete the masonry work as shown and specified. All concrete hallow block both existing and newly install shall be plastered both sides and smooth finished. Mortar shall be workable cement-sand mixture and attaining a 28 days compressive strength of 3.44 mPa (500 psi). No hand mixing shall be allowed during concreting operations.

The minimum size of reinforcement shall be 10 mm in diameter. Vertical reinforcement and horizontal reinforcement shall be as indicated in the plans. Vertical and horizontal reinforcement bars shall be continuous, lapped or spliced. All horizontal and vertical bars as the case maybe, shall be anchored 20 bars diameters into the concrete footings, columns and beams. All horizontal reinforcement shall be tied to the vertical reinforcement at every intersection with No. 16 GI Wire.

## **2.6 Painting**

The metal surfaces shall be clean, dry, and free from mill scale, rust, grease, oil, or any other substance that could affect the quality of the painting and it shall be well puttied and sand papered.

All surfaces to be painted and, before beginning any work, shall be ensure that work of other trade has been left or installed in workmanlike condition to receive paint.

Each coat of paint shall be applied at proper consistency and brushed/rolled evenly, free of brush marks, sags, runs, and with no evidence of poor workmanship. No painting shall be done under conditions of weather, moisture, or temperature unsuited to good work, nor until previous coat is hard and dry. Paints are of highest standard quality such as Davies or Boysen. All Painting materials shall be referred to the Owner.

3. All waste materials shall be cleared and properly disposed by the contractor.
4. Pull-out/Turn-over materials form shall be properly filled-out by the contractor prior to endorsement to GSCWD warehouse personnel.
5. The project duration is thirty (30) calendar days and shall commence five (5) days after the receipt of Notice to Proceed.
6. Authorized representative of General Santos City Water District shall be assigned to monitor/inspect the implementation of the project.
7. One (1) year warranty under normal condition shall be provided by the contractor.
8. The progress payment shall be made upon reaching 30%, 70% and 100% project completion.

Prepared by:



**DANILO M. HORLADOR JR., CE**  
PPDO-A

Checked by:



**MARIA CELIA N. DANDAN, CE**  
Department Manager - A

Approved by:



**ROGELIO A. BESANA JR., CE, RMP**  
Acting General Manager





Republic of the Philippines  
**GENERAL SANTOS CITY WATER DISTRICT**

E. Fernandez St. Lagao, General Santos City  
 Telephone No. (083) 552-3824/ Telefax No. (083) 553-4960  
 E-mail Address: gscwaterdistrict@yahoo.com



Project: **CONSTRUCTION OF ROADWAY PERIMETER FENCE AT P.S. NO. 27**  
 Location: **LANDERO LOT, BRGY. MABUHAY, GENERAL SANTOS CITY**  
 Owner: **GENERAL SANTOS CITY WATER DISTRICT**  
 Subject: **BILL OF QUANTITIES**

ITEM NO.	DESCRIPTION	QUANTITY	UNIT	UNIT COST	AMOUNT
<b>A.</b>	<b>EARTH WORKS</b>				
A.1	Backfilling	43.00	cu.m.		
A.2	Excavation	18.87	cu.m.		
<b>B.</b>	<b>DEMOLITION</b>				
B.1	Removal of Trees (Mango & Bamboo)	3.00	pcs.		
	<i>Including Hauling and Disposal</i>				
B.2	Demolition of Existing Fence	5.00	L.M.		
<b>C.</b>	<b>STRUCTURAL WORKS</b>				
C.1	Gravel Bedding	1.34	cu.m.		
	<i>Gravel 3/4" (with 15% shrinkage factor)</i>				
C.2	Reinforcing Bar Works	525.51	kgs.		
	<i>Rebarworks Fabrication and Installation of 10mm dia. def bars for stirrups and ties, 12mm dia. def. bars for main bars</i>				
C.3	Form Works	31.00	sq.m.		
	<i>Installation of 2" x 2" x 12' Coco Lumber for form works</i>				
	<i>Installation of 12mm Thickness Ordinary Plywood for form works</i>				
C.4	Concrete Works with Compressive Strength of 3000psi @28 days	5.21	cu.m.		
	<i>Concreting of footing, wall footing and columns</i>				
C.5	Masonry and Plastering Works	80.38	sq.m.		
	<i>Furnishing and Installation of 100mm thickness CHB with 10mm dia def. bar reinforcements</i>				
	<i>Furnishing and Plastering of 12mm thickness concrete plaster (one-face on wall of Existing Fence and one-face on New Fence along roadway)</i>				
<b>D.</b>	<b>STEEL GATE WORKS</b>				
D.1	Steel Gate (2-way Swing type) Fabrication and Installation	1.00	lot		
	<i>Furnishing and Installation of 50 x 100 x 1.0mm B.I. Tubular for gate framing</i>				
	<i>Furnishing and Installation of 50 x 75 x 1.0mm B.I. Tubular for gate framing</i>				

		<i>Furnishing and Installation of 50 x 25 x 1.0mm B.I. Tubular for gate framing</i>				
		<i>Furnishing and Installation of Pre-fabricated Barrel Bolt</i>				
<b>E.</b>	<b>PAINTING WORKS</b>					
	<b>E.1</b>	<b>Painting Works (Concrete &amp; Steel Gate)</b>	<b>100.00</b>	<b>sq.m.</b>		
		<i>Furnishing and Painting of Epoxy Primer Gray for Gate</i>				
		<i>Furnishing and Painting of Epoxy Enamel Paint for Gate</i>				
		<i>Furnishing and Painting of Acrylic Latex Paint Primer for Perimeter Fence</i>				
		<i>Furnishing and Painting of Acrylic Semi Gloss Paint for Perimeter Fence</i>				
<b>TOTAL PROJECT COST</b>						

**Note:**

**PLEASE REFER TO APPROVED PLAN FOR FURTHER DETAILS**

Submitted by \_\_\_\_\_ :

Date: \_\_\_\_\_

Name of representative of Bidder \_\_\_\_\_ :

Position: \_\_\_\_\_ :

Name of Bidder \_\_\_\_\_ :