Date



Republic of the Philippines GENERAL SANTOS CITY WATER DISTRICT

E. Fernandez Street, Barangay Lagao General Santos Telephone No.: 552-3824; Telefax No.: 553-4960 Email Address: gscwdprocurement@yahoo.com

REQUEST FOR QUOTATION

DATE: 7/16/2024

RFQ #:3-0724-057

SUPPLIER: ADDRESS: TELEPHONE NO. : TIN NO. :				
stating the sh representative subject to the Instructions: 1. Accompli 2. Do not a 3. If Techn (supplier /	e your lowest price on the item/s listed knortest time of delivery and submit you not later than 7/20/2024, Pls. furnish terms and conditions contained therein. sh this Request for Quotation duly, correctle the contents of this form in any way. ical Specifications/ Terms of Reference is particle provider) must indicate and signify in the specification.	r quotat this off Ly, and o	cion dul fice the completel	y signed by you following article Y. et bidder
ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	REPAIR CLAMP 8``: PLEASE SEE ATTACHED PICTURE-ABC: PHP 60,000.00 ###############################	10	pc	P
Pate of Delivery: Price Validity : Mode of Payment: Place of Delivery: *****No partial de Note: 6% WITHHOLDI PR NO.: 0624-045 Requested by: Appril 1. 1004	livery allowed**** ING TAX DEDUCTION	Price q	uoted by: Supp	lier



Republic of the Philippines
GENERAL SANTOS CITY WATER DISTRICT
E. Fernandez St., Brgy. Lagao, General Santos City
Telephone No. (083) 552-3824/ Telefax No. (083) 553-4960
E-mail Address: gscwaterdistrict@yahoo.com
www.gensanwater.gov.ph

Stainless Repair Clamp

















Single Band

Double Band

Safe Water... Our Thrust, Our Service, Our Commitment.



Republic of the Philippines GENERAL SANTOS CITY WATER DISTRICT

E. Fernandez St., Brgy. Lagao, General Santos City
Telephone No. (083) 552-3824/ Telefax No. (083) 553-4960
E-mail Address: gscwaterdistrict@yahoo.com
www.gensanwater.gov.ph





Size	OD	Length (mm)	Bolts	Working Pressure	Band
DN 50	58-68	300	M16 x 180mm	PN16	Single Band
DN 80	85-95	300	M16 x 180mm	PN16	Single Band
DN 100	105-115	300	M16 x 180mm	PN16	Single Band
DN 150	155-165	300	M16 x 180mm	PN16	Single Band
DN 200	220-230	300	M16 x 180mm	PN16	Single Band
DN 250	270-290	300	M16 x 180mm	PN16	Single Band
DN 300	305-325	300	M16 x 180mm	PN16	Single Band
DN 350	390-410	300	M16 x 180mm	PN16	Double Band
חחו אחח	440 460	300	M16 v 180mm	DN16	Double Rand

Parts	Materials
Body	SS304
Bridge Plate	SS304
Lockable Plate	SS304
Bolts-teflon	SS304 (teflon coated)
Nuts-teflon	SS304 (teflon coated)
Washer	SS304
Rubber Seal Gasket (Waffle Type Structure)	EPDM Rubber
Lugs	SS304

Main Parts

Body, Bridge Plate, Lockable Plate, Bolts, Nuts, and Washer must be stainless steel AISI 304 (A2)

Gasket

EPDM to BS EN681-1/NBR to EN682 Rubber must be WRAS(UK) approved EPDM Rubber for Normal Application

Lug

Stainless Steel to AISI 304 (A2)

Prepared by:

Clerk Processor B

Procurement, Quality Control and Property Division

Safe Water... Our Thrust, Our Service, Our Commitment.