



Republic of the Philippines
GENERAL SANTOS CITY WATER DISTRICT
 E. Fernandez Street, Barangay Lagao General Santos
 Telephone No.: 552-3824; Telefax No.: 553-4960
 Email Address: gscwdprocurement@yahoo.com

GPM-014-4

REQUEST FOR QUOTATION

RFQ #: 3-0824-011 DATE: 8/6/2024

SUPPLIER: _____
 ADDRESS: _____
 TELEPHONE NO. : _____
 TIN NO. : _____

Dear Sir/Madam,

Pls. quote your lowest price on the item/s listed below subject to general condition stating the shortest time of delivery and submit your quotation duly signed by your representative not later than 8/10/2024, Pls. furnish this office the following articles subject to the terms and conditions contained therein.

Instructions :

1. Accomplish this Request for Quotation duly, correctly, and completely.
2. Do not alter the contents of this form in any way.
3. If Technical Specifications/ Terms of Reference is provided, prospect bidder (supplier / service provider) must indicate and signify compliance to every parameter in the specification.

ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	MIRRORLESS CAMERA : PLS SEE ATTACHED TECHNICAL SPECIFICATION-ABC: PHP 130,000.00 ##### nothing follows #####	1	unit	P

Date of Delivery: _____
 Price Validity : _____
 Mode of Payment: _____

Place of Delivery: GSCWD Bodega
 *****No partial delivery allowed*****
 Note: 6% WITHHOLDING TAX DEDUCTION
 PR NO.: 0824-004

Requested by:

Price quoted by:

ANDREW N. NADAL, JR.
 Material Procurement Officer A

 Supplier

 Date



TECHNICAL SPECIFICATION

TITLE: PURCHASE OF MIRRORLESS CAMERA WITH 28-70MM LENS AND ACCESSORIES KIT

I. Scope of the Contract

Supply of mirrorless camera with 28-70mm lens and accessories kit.


II. Specification

MIRRORLESS CAMERA (BODY)	
Sensor Resolution	Actual: 25.3 Megapixel Effective: 24.2 Megapixel (6000 x 4000)
Image Sensor	35.6 x 23.8 mm (Full-Frame) CMOS
Image Stabilization	Sensor-Shift, 5-Axis
ISO Sensitivity Range	Photo 100 to 51,200 in Manual Mode (Extended: 50 to 204,800) 100 to 12,800 in Auto Mode Video 100 to 51,200 in Manual Mode (Extended: 102,400) 100 to 12,800 in Auto Mode
Continuous Shooting	Up to 10 fps at 24.2 MP for up to 89 Frames (Raw) / 177 Frames (JPEG)
Internal Recording Modes	H.264/XAVC S UHD 4K (3840 x 2160) at 23.98/25/29.97 fps [60 to 100 Mb/s] 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [16 to 100 Mb/s] AVCHD/H.264 1920 x 1080i at 50/59.94 fps [17 to 24 Mb/s]
External Recording Modes	4:2:2 8-Bit via HDMI UHD 4K (3840 x 2160) at 23.98/25/29.97 fps 1920 x 1080p at 23.98/50/59.94 fps 1920 x 1080i at 50/59.94 fps
Media/Memory Card Slot	Slot 1: SD/SDHC/SDXC (UHS-II) Slot 2: SD/SDHC/SDXC/Memory Stick Duo Hybrid (UHS-I)
Video I/O	1x Micro-HDMI (Unspecified Signal) Output
Audio I/O	1x 1/8" / 3.5 mm TRS Stereo Headphone Output 1x 1/8" / 3.5 mm TRS Stereo Microphone Input
Power I/O	1x USB-C Input/Output
Wireless Connection	Wi-Fi 4 (802.11n), Bluetooth 4.1, NFC
Display Type	Tilting Touchscreen LCD; 3" display; 921,600 Dot Resolution
Battery Type	1x NP-FZ100 Rechargeable Lithium-Ion, 7.2 VDC, 2280 mAh (Approx. 610 Shots)
Flash	Modes: Auto, Fill Flash, Hi-Speed Sync, Off, Rear Sync, Red-Eye Reduction, Slow Sync, Wireless Maximum Sync Speed: 1/250 Second External Flash Connection: Shoe Mount




Viewfinder	Built-In Electronic; 0.5" size; 23mm eyepoint
Shoe Mount	1x Intelligent Hot Shoe
Tripod Mounting Thread	1x 1/4"-20 Female (Bottom)
Material of Construction	Magnesium Alloy
Dimensions (W x H x D)	5 x 3.8 x 2.9" / 126.9 x 95.6 x 73.7 mm
Weight	1.43 lb / 650 g
MIRRORLESS CAMERA LENS (28-70mm f/3.5-5.6 OSS)	
Focal Length	28 to 70mm
Maximum Aperture	f/3.5 to 5.6
Lens Format Coverage	Full-Frame
Focus Type	Autofocus
Image Stabilization	Yes
Filter Size	55 mm (Front)
Dimension	72.5 x 83 mm
Weight	10.41 oz / 295 g
ACCESSORIES	
Battery Pack with charger	
Camera Bag and Strap	
SD CARD 128GB UHS-I SDXC	
DESIGN: SEE ATTACHED PHOTO	

Prepared by:


EnP Vanne Thea G. Balboa, MPA
Senior Community Relations Officer

Noted by:


Atty. Judy A. Lim-Pasman
Acting Division Manager
LSMOA

MIRRORLESS CAMERA WITH 28-70MM LENS

