



Republic of the Philippines
GENERAL SANTOS CITY WATER DISTRICT
E. Fernandez Street, Barangay Lagao General Santos
Telephone No.: 552-3824; Telefax No.: 553-4960
Email Address: gscwdprocurement@yahoo.com

GPM-014-4

REQUEST FOR QUOTATION

RFQ #: 3-1023-023 DATE: 10/10/2023

SUPPLIER: _____
ADDRESS: _____
TELEPHONE NO. : _____
TIN NO. : _____

Dear Sir/Madam,

Pls. quote your lowest price on the item/s listed below subject to general condition stating the shortest time of delivery and submit your quotation duly signed by your representative not later than 10/14/2023, Pls. furnish this office the following articles subject to the terms and conditions contained therein.

Instructions :

1. Accomplish this Request for Quotation duly, correctly, and completely.
2. Do not alter the contents of this form in any way.
3. If Technical Specifications/ Terms of Reference is provided, prospect bidder (supplier / service provider) must indicate and signify compliance to every parameter in the specification.

ITEM NO.	DESCRIPTION	QTY.	UNIT	UNIT PRICE
1	LUBRICANT GREASE : WITH ATTACHED SPECIFICATION-ABC: PHP 74,000.00 ##### nothing follows #####	2	PAIL	P

Date of Delivery: _____
Price Validity : _____
Mode of Payment: _____

Place of Delivery: GSCWD Bodega

****No partial delivery allowed****

Note: 6% WITHHOLDING TAX DEDUCTION

PR NO.: 1023-010

Requested by:

Price quoted by:

RICHARD H. NADAL JR.
Procurement Officer - Assistant A

Supplier

Date



GENERAL SANTOS CITY WATER DISTRICT
E. Fernandez St., Brgy. Lagao, General Santos City
Telephone No. (083) 552-3824; Telefax No. 553-4966
www.gensanwater.gov.ph



Omega Super Bearing Grease Specification:

1. Quality engineered for use in a wide variety of high impact and extreme pressure conditions.
2. Contains super supplements and Omega's exclusive "Megalite" additives that form a wear-resistant film on metal surfaces to minimize metal-to-metal contact.
3. Formulated for excellent resistance to water protects working surfaces against corrosion and oxidation.
4. Provides the greatest "Margin of protection", having a minimum Dropping Point of **249°C** (480°F). Sets up its own seal againsts dirt, dust and water.

Chemwerke 77RRP Liquid Passivator and Rust Remover Concentrate Specification:

1. Removes rust efficiently and prevents oxidation. It converts existing rust into part of metal and passivates the surface to prevent further rusting.
2. It is non flammable and no foul odor.
3. Requires no neutralizing or post application treatment like ordinary rust remover does.

Application Procedure:

1. Thorough cleaning of all existing rust and other surface contamination by grinding, sanding, wire brushing or sand/grit-blasting if possible.
2. Dilute CW 77RRP with 2 parts of water on lightly rusted parts applications.
3. Dilute CW 77RRP with 1 parts of water on medium rusted parts applications.
4. Use full concentration of CW 77RRP on heavily rusted parts. You may also opt to dip small parts for total rust removal.
5. Re-application after 45 minutes is required on extremely rusted parts.

Prepared by:

Darwin Dave D. Sarsale
Engineering Assistant B

Noted by:

Jeremias A. Reyes Jr. MPA
OIC- Department Manager A